

Ref. : RACC6141.pas

Rev. : Initial

Date : 20/04/2015

Page : 1/1

SYMETRICAL COUPLING

RACC 6141



Tecofi'
VALVE DESIGNER - FRANCE

APPLICATION

General use : Irrigation, network fire, hydrocarbon, common fluids.

GENERAL CHARACTERISTICS

Stainless steel ASTM A351 CF8M female coupling with lock.
Complies to NF-E 29572.

CONSTRUCTION

Stainless steel ASTM A351 CF8M body.
FKM gasket.
Stainless steel snap ring.

DIMENSIONS

DN		Ø E	Ø C	L1	L2	Weight (kg)
mm	inch					
20	3/4"	32	19	73	15	0,22
25	1"	38	24	73	15	0,27
32	1" 1/4	50	29	73	14	0,35
40	1" 1/2	55	40	86	16	0,4
50	2"	64	50	90	17	0,77
65	2" 1/2	78	65	89	22	0,89
80	3"	101	80	106	26	1,35
100	4"	120	100	132	26	2,33

WORKING CONDITIONS

Maximum working temperature: -10°C / +180°C
Working pressure : 16 bar.

STANDARDS

Fabrication according to ISO 9001 : 2008
Construction according to NF-E 29572
Threaded BSP cylindrical according to NF EN ISO 228-1

