

Ref. : RACC6142.pas

Rev. : Initial

Date : 20/04/2015

Page : 1/1

SYMETRICAL COUPLING

RACC 6142



Tecofi'
VALVE DESIGNER - FRANCE

APPLICATION

General use : Irrigation, network fire, hydrocarbon, common fluids.

GENERAL CHARACTERISTICS

Stainless steel ASTM A351 CF8M coupling without lock.
Complies with NF-E 29572

CONSTRUCTION

Stainless steel ASTM A351 CF8M body.

DIMENSIONS

DN		Ø E	Ø C	L1	L2	L3	Weight (kg)
mm	inch						
20	3/4"	20	20	37	19,2	12	0,09
25	1"	26	26	43	19,7	13	0,15
32	1" 1/4	30	30	43,5	21,5	13,5	0,26
40	1" 1/2	41	41	53	27,5	15	0,29
50	2"	52	54	65	36	18	0,55
65	2" 1/2	66	67	65	34	20	0,74
80	3"	79	82	78	39	24	0,93
100	4"	100	101	83	42	25	1,53

WORKING CONDITIONS

Maximum working temperature: -10°C / +180°C
Working pressure : 16 bar.

STANDARDS

Fabrication according to ISO 9001 : 2008
Construction according to NF-E 29572
Threaded BSP male cylindrical according to NF EN ISO 228-1

