

Ref. : RACC6144.pas

Rev. : Initial

Date : 20/04/2015

Page : 1/1

SYMETRICAL FEMELLE COUPLING WITHOUT LOCK

RACC 6144



Tecofi'
VALVE DESIGNER - FRANCE

APPLICATION

General use : Irrigation, network fire, hydrocarbon, common fluids.

GENERAL CHARACTERISTICS

Stainless steel ASTM A351 CF8M female coupling without lock.
Complies to NF-E 29572.

CONSTRUCTION

Stainless steel ASTM A351 CF8M body.

DIMENSIONS

DN		Ø E	Ø C	L1	L2	L3	Weight (kg)
mm	inch						
15	1/2"	27	15	30	16,5	13,5	0,07
20	3/4"	31	20	33	19,2	12	0,07
25	1"	37	25	34	19,7	14	0,09
32	1 1/4"	48	30	48	21,5	14	0,24
40	1 1/2"	54	40	42	27,5	16	0,19
50	2"	68	51	49	36	18	0,37
65	2 1/2"	83	65	53	34	21	0,48
80	3"	101	82	59	39	26	0,93
100	4"	121	101	63	42	26	0,89

WORKING CONDITIONS

Maximum working temperature: -10°C / +180°C
Working pressure : 16 bar.

STANDARDS

Fabrication according to ISO 9001 : 2008
Construction according to NF-E 29572
Threaded BSP cylindrical according to NF EN ISO 228-1

