

Ref. : RACC6503.pas

Rev. : Initial

Date : 21/04/2015

Page : 1/1

# REDUCED HOSE COUPLING WITH LOCK AND COLLAR

## RACC 6503



**Tecofi'**  
VALVE DESIGNER - FRANCE

### APPLICATION

General use : Irrigation, network fire, hydrocarbon, common fluids.

### GENERAL CHARACTERISTICS

Stainless steel ASTM A351 CF8M couplings with lock and collar  
Complies to NF-E 29572.

### CONSTRUCTION

Stainless steel ASTM A351 CF8M body.  
FKM gasket.  
Stainless steel snap ring.

### DIMENSIONS

DN		Ø F	Ø E	Ø C	L1	L2	L3	Weight (kg)
mm	inch							
40	1" 1/2	40	33	39	93	27	35	0,49
50	2"	51	44	50	123,5	36	49	0,96
65	2" 1/2	63	56	66	126	34	59	1,21
80	3"	76	67	81	145	39	59	1,9
100	4"	100	92,5	100	162	42	67	3,11

### WORKING CONDITIONS

Maximum working temperature: -10°C / +180°C  
Working pressure : 16 bar.

### STANDARDS

Fabrication according to ISO 9001 : 2008  
Construction according to NF-E 29572

