

Ref. : RACC8141.pas

Rev. : Initial

Date : 07/09/2016

Page : 1/1

REDUCED FEMALE THREADED SYMETRICAL COUPLING WITH LOCK

RACC 8141



APPLICATION

General use : Irrigation, network fire, hydrocarbon, common fluids.

GENERAL CHARACTERISTICS

Aluminium couplings
White NBR with lock
Complies to NF-E 29572.

CONSTRUCTION

Aluminium body.
NBR gasket.
Steel snap ring.

DIMENSIONS

DN		Ø E	Ø C	L1	L2	Weight (kg)
mm	inch					
20	3/4"	30	20	59	12,0	0,05
25	1"	42	24	68	14,5	0,09
32	1"1/4	48	30	68	14,0	0,12
40	1"1/2	56	39	86	17,0	0,21
50	2"	68	49	106	21	0,37
65	2"1/2	84	64	109	22	0,44
80	3"	94	80	103	26	0,76
100	4"	122	97	136	27	1
150	6"	180	150	120	37	2,35

WORKING CONDITIONS

Maximum working temperature: -10°C / +180°C
Working pressure : 16 bar.

STANDARDS

Fabrication according to ISO 9001 : 2008
Construction according to NF-E 29572
Threaded connection according to NF EN ISO 228-1.

