

Ref. : VP 5445-02.pas

Rev. : C

Date : 26/11/2012

Page : 1/1

BUTTERFLY VALVE WITH HANDLE

VP 5445-02



Tecofi'
VALVE DESIGNER - FRANCE

APPLICATION

General use : Water, air, acids etc.

GENERAL CHARACTERISTICS

Design in accordance with NF EN 593.

TECFLY type with lugs enabling use on bottom line.

Tightness in both ways.

Two kinds of sleeves:

- Body in dovetail shape ensures a perfect assembling (for high vacuum we can stick it)

- Internally reinforced aluminium sleeve giving a lower torque

Stem: high and low semi stem giving a high flow coefficient.

Machined disc with on periphery giving a low and regular torque.

Stem unjectable, bearing:stainless steel teflon lined.


Dovetail type sleeve, mounting flange according to ISO 5211.

Handle in ductile iron very resistant : notched, locked notch, regulating option.

It's easy to change the locked notched type into a regulating handle, without disassembling.

CONSTRUCTION

15	1	Screw	Stainless steel A2	
14	2	Nut	Stainless steel A2	
13	2	Spring washer	Stainless steel A2	
12	2	Screw	Stainless steel A2	
11	1	Handle	Ductile iron	
10	1	Indicator	Aluminium	
9	2	Split pin	Sainless steel	
8	1	Gasket	NBR	
7	2	O-ring	NBR	
6	2	Guiding bearing	Teflon-lined	
5	1	Upper stem	Stainless steel 416	DIN: 1.4005 ASTM: AISI 416 BS: 416 S21
4	1	Lower stem	Stainless steel 416	DIN: 1.4005 ASTM: AISI 416 BS: 416 S21
3	1	Sleeve	Heat EPDM	
2	1	Disc	Steel A216 Grade WCB	DIN: GS-C25 ASTM: A216 Grade WCB BS: 161 Grade 430E
1	1	Body	Steel A216 Grade WCB	DIN: GS-C25 ASTM: A216 Grade WCB BS: 161 Grade 430E
Pos.	Qty.	Description	Material	



DIMENSIONS

DN	L	G	H	H1	V	Type	Weight (kg)
40 - 1"1/2	33	66	184	133	180	F07	3,0
50 - 2"	43	72	190	140	180	F07	3,7
65 - 2"1/2	46	78	203	153	180	F07	4,3
80 - 3"	46	89	209	159	180	F07	4,9
100 - 4"	52	102	228	178	220	F07	6,4
125 - 5"	56	117	240	190	220	F07	8,2
150 - 6"	56	130	253	203	220	F07	9,7
200 - 8"	60	159	288	238	318	F10	17,2
250 - 10"	68	190	318	268	318	F10	25,6
300 - 12"	78	222	356	306	318	F10	36,0

WORKING CONDITIONS

Maximum working pressure : 16 bar.

Maximum temperature : -15°C / +130°C.

Peak temperature : -30°C / +150°C.

Tightness in option	Maximum temperature	Peak temperature
EPDM	+4°C / +110°C	-20°C / +130°C
CSM (Type Hypalon®)	+4°C / +80°C	-20°C / +110°C
FPM (Type Viton®)	-10°C / +170°C	-20°C / +200°C
Silicone	-20°C / +170°C	-40°C / +200°C
Nitrile (NBR)	-10°C / +80°C	-20°C / +90°C

STANDARDS

Face to face according to standard NF EN 558-1serie 20, ISO 5752 serie 20, DIN 3202.

Mounting between flanges PN10 / PN16 : according to EN 1092-1, BS450, ANSI B16.1-5.

Adjustable between flanges ASA 150.

Pressure test according to standards

EN 12266-1, DIN 3230, BS 6755 and ISO 5208 :

Body : 24 bar.

Seat : 17,6 bar.

TECOFI France - 83, Rue Marcel Mérieux 69960 Corbas - FRANCE

Tél. +33 (0) 4 72 79 05 79 - Fax +33 (0) 4 78 90 19 19 / +33 (0) 4 72 79 05 70

Adresses e-mail : sales@tecofi.fr ; tecofi@tecofi.fr / Site web : www.tecofi.fr